

XG3-10kW

Single Phase On-Grid Solar Inverter



**Efficient
Higher revenue**

- 2 MPP Trackers , Max. input current per string: 18A
- 150% DC Input Oversizing
- Compatible with high power modules



**Intelligent
Simple O&M**

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- Intelligent Fault Detection: ac-side voltage and current waveforms real-time recorded, fast fault location
- Support RS485/WiFi/4G: remote monitoring and operation via PC or mobile phones



**Reliable
Worry free**

- IP66 Protection Degree: support outdoor installation
- DC & AC Type II SPD: prevent lightning damage
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

	XG3KTL-1M	XG3KTL	XG3K6TL	XG4KTL	XG4K2TL	XG4K6TL	XG5KTL	XG6KTL	XG7KTL	XG8KTL	XG9KTL	XG10KTL	XG7KTL1	XG8KTL1	XG9KTL1	XG10KTL1
--	-----------	--------	---------	--------	---------	---------	--------	--------	--------	--------	--------	---------	---------	---------	---------	----------

Input (DC)																	
Max. Input Power	4.5kW	4.5kW	5.52kW	6kW	6.3kW	6.9kW	7.5kW	9kW	10.5kW	12kW	13.5kW	15kW	10.5kW	12kW	13.5kW	15kW	
Max. Input Voltage	600V																
Start Voltage	80V																
Rated Input Voltage	360V																
Full-load MPP Voltage Range	190V ~ 480V	120V ~ 480V	135V ~ 480V	145V ~ 480V	150V ~ 480V	160V ~ 480V	170V ~ 480V	190V ~ 480V	230V ~ 480V	250V ~ 480V	270V ~ 480V	290V ~ 480V	230V ~ 480V	250V ~ 480V	270V ~ 480V	290V ~ 480V	
MPPT Voltage Range	80V ~ 560V																
Number of MPP Trackers	1	2															
Number of String per MPPT	1	1/1											1/2				
Max. Current per MPPT	20A											15A / 25A					
Max. Short Circuit Current per MPPT	25A											18A / 30A					

Output (AC)																
Max. Output Current	15A	16A	20A	21A	23A	25A	27.3A	31.8A	36.4A	41A	45.5A	31.8A	36.4A	41A	45.5A	
Rated Output Power	3kW	3.68kW	4kW	4.2kW	4.6kW	5kW	6kW	7kW	8kW	9kW	10kW	7kW	8kW	9kW	10kW	
Max. Output Power	3.3kVA	3.68kVA	4.4kVA	4.62kVA	5kVA	5.5kVA	6kVA	7kVA	8kVA	9kVA	10kVA	7kVA	8kVA	9kVA	10kVA	
Rated Grid Frequency	50Hz / 60Hz															
Rated Grid Voltage	220Vac / 230Vac / 240Vac															
Power Factor	>0.99 (0.8 leading~0.8 lagging)															
THDi	<3% (Rated Power)															

Efficiency																
Max. Efficiency	98.10%		98.30%					98.10%								
European Efficiency	97.10%		97.20%					97.10%								
MPPT Efficiency	99.90%															

Protection																
DC reverse polarity protection	Yes															
Anti-islanding protection	Yes															
AC short circuit protection	Yes															
Residual current monitoring unit	Yes															
Insulation resistance monitoring	Yes															
Ground fault monitoring	Yes															
Grid monitoring	Yes															
PV string monitoring	Yes															
Surge protection	Type II															
AFCI protection	Optional															

Communication																
Display	LED / LCD / WiFi+App															
Communication	RS485 / WiFi / 4G															

Standard Compliance																
Grid Connection Standards	IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE-AR-N 4110:2018, VDE-AR-N 4105:2018, VDE-AR-N 4120:2018, EN 50549, AS/NZS 4777.2:2020, CEI 0-21, VDE 0126-1-1/A1 VFR 2014, UTE C15-712-1:2013, DEWA DRRG, NRS 097-2-1, MEA/PEA, C10/11, G98/G99															
Safety / EMC	IEC 62109-1:2010, IEC 62109-2:2011, EN 61000-6-2:2005, EN 61000-6-3:2007/A1:2011															

General Data																	
Dimensions (W x H x D)	380 x 380 x 160 mm																
Weight	13kg																
Operating Temperature Range	-30° C ~ +60° C																
Cooling Method	Natural										Smart forced air cooling			Natural			
Protection Degree	IP66																
Max. Operating Altitude	4000m																
Relative Humidity	0 ~ 100%																
Topology	Transformerless																
Night Power Consumption	<1W																

- a: For AS4777, Rated Output Power of XG5KTL is 4999W.
- b: For VDE-AR-N 4105, Max. Output Power of XG4K6TL is 4600VA. For AS4777, Max. Output Power of XG4K6TL is 4999VA.
- c: For AS4777, Max. Output Power of XG5KTL is 4999VA.
- d: For AS4777, Max. Output Current of XG4K6TL and XG5KTL is 21.7A.

INVT Solar

